

# Super High-Resolution DayNight Dome Camera

# SCC-B5366/B5368 NEW



## Features

- 1/3" SONY 410K/470K Pixels Super-HAD IT CCD
- High Resolution : 600 TV Lines
- Min . illumination 0.00023Lux (F1.2, 15 IRE, Sens-Up 512x)
- SCC-B5366 : f=2.5~6 mm, Auto Iris Lens  
SCC-B5368 : f=2.9~10 mm, Auto Iris Lens
- Internal/Linelock (Phase Control) Function
- Day/Night Function (Soft), Sens-Up Function (512x)
- Motion Adaptive Digital Noise Reduction (3D+2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function
- eXtended Dynamic Range (XDR)
- Privacy Mask Function (Polygonal Mosaic)
- DIS (Digital Image Stabilization)
- CCVC (Camera Control Via Coaxial cable, Controller: SCX-RD100)
- Multi-Language OSD support
- Intelligent Video (Moved / Fixed / Fence / Area / Tracking)
- DC12V & AC24V 60Hz(50Hz)

## Specifications

Model	SCC-B5366	SCC-B5368	
Camera Type	Color/BW		
	Color		
Image	Device		
	1/3" Super-HAD IT CCD		
Image	Pixels	Effective	
	768 x 494 / 752 x 582		
Scanning	System		
	Interface		
	Horizontal	Internal Mode	
	Frequency	Line-lock Mode	
Scanning	Vertical	Internal Mode	
	Frequency	Line-lock Mode	
Resolution	Horizontal		
	600 TV Lines		
Min. Scene	Sens-up off		
Illumination	0.12Lux(15 IRE), 0.2Lux(30 IRE), 0.4Lux(50 IRE) @F1.2		
Illumination	Sens-up		
	0.00023Lux(15 IRE), 0.0005Lux(30 IRE), 0.0008Lux(50 IRE) @F1.2		
Functions	Number of Privacy Zone		
	12 (Polygonal Method)		
	Day/Night		
	Color/BW/AUTO (Soft)		
	Motion Detection		
	Off/On		
	D-Zoom		
	1x ~16x (0.1x STEP)		
	High Speed Shutter	1/60~1/10Ksec(OSD)	1/50~1/10Ksec(OSD)
	Sens Up	2x ~ 512x	
	BLC / AGC	Off/On / Off/On	
	Line Lock	Off/On (Phase Control)	
	Camera ID	Off/On (Max.54ea/2Lines)	
	White Balance	ATW1/ATW2/AWC/MANUAL	
	eXtended Dynamic Range	Off/Low/Mid/High	
	Digital Noise Reduction	Off/On	
	Digital Image Stabilization	Off/On	
Intelligent Video	Off/On (Moved / Fixed / Fence / Area / Tracking)		
PIP	Off/On		
Etc. Function	Detail, Reverse(H/V), Posi/Nega		
Video Output	VBS 1.0Vp-p	VBS 1.0VpN/Ap	
S/N Ratio	52 dB		
Lens	Focal Length		
	2.5~6mm		
	Aperature Ratio		
	F1.2		
	Viewing Angle	Tele	28.8°(H) x 21.6°(V)
	Wide	94.6°(H) x 68.4°(V)	
	Lens Drive Type / Mount Type		
	AI(DC) / Board Type		
Remote Control	CCVC	Yes (with SCX-RD100)	
	RS485	Yes (Multi Protocol, 8ea)	
Environmental Conditions	Operating Temperature		
	Absolute : -10°C ~ +50°C / Sustained : -20°C ~ +60°C		
	Operating Humidity		
	Less than 90%		
Power	Power Requirement		
	24 VAC ±10%/12 VDC ±10%		
Physical Specification	Dimensions		
	102(ø) x 78(H) mm		
	Weight		
	330 g		
	Color	Body	
		White	

## Dimensions (unit:mm)

